

PROTEX

Central Heating System Accessories



WIRELESS INSPECTION CAMERA WITH COLOR LCD MONITOR

DIRECTIONS FOR USE

INSTALLATION

Please install the battery tube first before using the product, and choose the accessory according to the actual situation. Steps of installation are as following:

To install batteries

1. Using a screwdriver, remove screw and cover.
2. Remove battery compartment and insert four new AA batteries into the proper slots in the battery compartment. Proper battery orientation is indicated on the battery compartment.
3. Reinstall battery compartment and battery cover and screw as before

NOTE Dry your hands before installation or replacing batteries.

To Install The Camera With Flexible Tube

Connect the camera with tube to the body, make sure the keyed ends are properly aligned. Once they are aligned, finger tighten the knurled knob to hold the connection in place.

To Install Accessory

The three included accessories, (mirror, hook and magnet) all attach to the imaging head the same way. To connect, hold the imaging head, Slip the end of the accessory, over the flats of the imaging head.

To Install Monitor for Wired Use

The product also supports wired use by connecting the monitor to camera.

Connect To Monitor Power

Plug the connect cable into power socket of monitor, and plug the end of connect cable into adapter, then connect the adapter to 8V~24V power, the power indicator will lights on red, which indicates being charging. The built-in Li-battery will be charged after the adapter is plugged in, and the red indicator lights up during charging and will turn off after a full charge.

To Connect Display Device

When you need connect a display device please connect the monitor to display device with video output cable.

OPERATION

1. Roll the ON/OFF switch to turn ON the camera, and power indicator will lights, The switch then acts as dimmer for the twin LEDs that surround the camera on the imager head and provide lighting.
2. Slide the ON/OFF switch to ON, and power indicator will lights on green, the pictures display on LCD, adjust brightness, contrast, orientation, and roll the ON/OFF witch of the camera for better image effect.
3. When in use, the tube should easily maneuver itself into position going forward.
TIP The flexible tube can be bent into a certain shape. This may help you explore the tube into narrow areas.
4. The accessories of Handhold Inspection camera can be used to retrieve small items like dropped rings or screw.