

PROTEX

Central Heating System Accessories



WIRELESS INSPECTION CAMERA WITH COLOR LCD MONITOR

TECHNICAL DATA

CAMERA

Mode No.	GB8802
Imaging Sensor	CMOS
Total Pixels	704 x 576 (PAL); 712 x 486 (NTSC)
Horizontal View Angle	50 degree
Transmission Frequency	2468MHz
Minimum Illumination	0 Lux
Modulation Type	18MHz
Power Supply	4 x AA Batteries
Waterproof Capacity	IP 67 (only for imager head)
Dimensions (W x D x H)	186 x 145 x 41 (mm) (Exclude Flexible Tube)
Weight	~ 530g

MONITOR

Mode No.	GB7802
LCD Screen Type	2.36" TFT-LCD
Effective Pixels	480 x 240
Video System	PAL/NTSC
Transmission Frequency	2468MHz
Exterior Supply Voltage	8V-24V DC
Consumption Current (Max.)	490mA
Video Output Level	0.9-1.3Vp-p@75ohm
Dimensions (W x D x H)	100 x 70 x 30 (mm)
Weight	~ 140g
Operating Temperature	-10°C ~+50°C / +14°F ~+122°F
Operating Humidity (Max.)	15~85%RH

* Actual transmission range may vary according to the water, location, interference and building construction.

* All the specifications are subject to minor change without prior notice.